



U-Type Hot-Rolled Piles	W mm	H mm	T mm	Unit Mass kg/Lin m	Unit Mass kg/m ² *	Sectional Area cm ² /m*	Section Modulus cm ³ /m*	Moment of Inertia cm ⁴ /m*
SP1 A	400	85	8.0	35.5	88.8	45.2	529	4,500
SP2	400	100	10.5	48.0	120.0	61.2	874	8,740
SP2 A	400	120	9.2	43.2	108.0	55.0	880	10,600
SP2 W	600	130	10.3	61.8	103	131.2	1000	13000
STU 1000	600	130	10.3	61.8	103	131.2	1000	13000
SP3	400	125	13.0	60.0	150	191.0	1310	16400
SP3 A	400	150	13.1	58.4	146	186.0	1520	22800
SP3 W	600	180	13.4	81.6	136	173.2	1800	32400
STU 1800	600	180	13.4	81.6	136.0	173.2	1800	32400
SP4W	600	210	18.0	106.0	177.0	225.5	2700	56700
STU 2700	600	210	18.0	106.0	177.0	225.5	2700	56700
L 755	750	225	11.7	95.6	127.5	162.4	2000	45000
L 703	700	200	9.5	67.5	96.4	123.0	1210	24200

U-Type Hot-Rolled Piles	W mm	H mm	T mm	Unit Mass kg/Lin m	Unit Mass kg/m ² *	Sectional Area cm ² /m*	Section Modulus cm ³ /m*	Moment of Inertia cm ⁴ /m*
L 703 K	700	200	10.0	72.1	103.0	131.0	1300	25950
L 703 10/10	700	200	10.0	75.6	108.0	138.0	1340	26800
L 704	700	200	10.2	80.5	115.0	146.0	1600	35200
L 600	600	75	9.5	56.4	94.0	120.0	510	3825
L 600 K	600	75	10.0	59.4	99.0	126.0	540	4050
L 601	600	155	7.5	46.8	78.0	98.0	745	11520
L602	600	155	8.2	53.4	89.0	113.0	830	12870
L 603	600	155	9.7	64.8	108.0	138.0	1200	18600
L 603 K	600	155	10.0	68.1	113.5	145.0	1240	19220
L 603 10/10	600	155	10.0	69.6	116.0	148.0	1260	19530
L 604 n	600	190	10.0	73.8	123.0	157.0	1600	30400
L 605	600	210	12.5	83.5	139.2	177.0	2020	42420
L 605 K	600	210	12.2	86.7	144.5	184.0	2030	42630
L 606 n	600	217	14.4	94.2	157.0		2500	54375
L 628	600	228	16.3	99.3	165.5		2780	63380
L 607 n	600	226	19.0	114.0	190.0	242.0	3200	72320
L 22 10/10	500	170	10.0	65.0	130.0	165.0	1300	22100
L 23	500	210	11.5	77.5	155.0	197.0	2000	42000
L 24	500	210	15.6	87.5	175.0	223.0	2500	52500
L 24/12	500	210	15.6	92.7	185.4	236.0	2550	53610
L 25	500	210	20.0	103.0	206.0	103.0	3040	63840
L 43	500	210	12.0	83.0	166.0	83.0	1660	34900

U-Type Hot-Rolled Piles	W mm	H mm	T mm	Unit Mass kg/Lin m	Unit Mass kg/m ² *	Sectional Area cm ² /m*	Section Modulus cm ³ /m*	Moment of Inertia cm ⁴ /m*
LX8	600	155	8.2	54.6	91.0		830	12,861
LX12	600	155	9.7	63.9	106.4		1,208	18,723
LX16	600	190	10.5	74.1	123.5		1,641	31,175
LX20	600	215	12.5	83.2	138.6		2,022	43,478
LX25	600	225	15.8	94.0	156.7		2,525	56,824
LX32	600	225	21.5	113.9	189.8		3,201	72,028
LX38	600	230	22.5	140.4	234.0		3,805	
AU 14	750	204	10.0	77.9	103.8	132.3	1405	28660
AU 16	750	205	11.5	86.3	115.0	146.5	1600	32850
AU 17	750	206	12.0	89.0	118.7		1665	34270
AU 18	750	220	10.5	88.5	118.0	150.3	1780	39300
AU 20	750	222	12	96.9	129.2	164.6	2000	44440
AU 21	750	222	12.5	99.7	132.9		2075	46180
AU 23	750	223	13	102.1	136.1	173.4	2270	50700
AU 25	750	225	14.5	110.4	147.2	187.5	2500	56240
AU 26	750	225	15	113.2	150.9		2580	58140
PU 12	600	180	9.8	66.1	110.1	140.0	1200	21600
PU 12S	600	180	10	71.0	118.4	150.8	1260	22660
PU 18-1	600	215	10.2	72.6	121.0	154.2	1670	35950
PU 18	600	215	11.2	76.9	128.2	163.3	1800	38650
PU 18+1	600	215	12.2	81.1	135.2	172.3	1920	41320
PU 22-1	600	225	11.1	81.9	136.5	173.9	2060	46380

U-Type Hot-Rolled Piles	W mm	H mm	T mm	Unit Mass kg/Lin m	Unit Mass kg/m ² *	Sectional Area cm ² /m*	Section Modulus cm ³ /m*	Moment of Inertia cm ⁴ /m*
PU 22	600	225	12.1	86.1	143.6	182.9	2200	49460
PU 22+1	600	225	13.1	90.4	150.7	192.0	2335	52510
PU 28-1	600	226	14.2	97.4	162.3	206.8	2680	60580
PU 28	600	227	15.2	101.8	169.6	216.1	2840	64460
PU 28+1	600	228	16.2	106.2	177.1	225.6	3000	68380
PU 32-1	600	226	18.5	109.9	183.2	233.3	3065	69210
PU 32	600	226	19.5	114.1	190.2	242	3200	72320
PU 32+1	600	226	20.5	118.4	197.3	251.3	3340	75410
GU 6N	600	154	6	41.9	69.9	89	625	9670
GU 7N	600	155	6.5	44.1	73.5	93.7	675	10450
GU 7S	600	155	7.2	46.3	77.1	98.2	740	11540
GU 7HWS	600	156	7.3	47.4	79.1	100.7	745	11620
GU 8N	600	156	7.5	48.5	80.9	103.1	770	12010
GU 8S	600	156	8	50.8	84.6	107.8	820	12800
GU 10N	600	158	9	55.8	93.0	118.5	995	15700
GU 11N	600	159	10	60.2	100.4	127.9	1095	17450
GU 12N	600	160	11	64.6	107.7	137.2	1200	19220
GU 13N	600	209	9	59.9	99.8	127.2	1270	26590
GU 14N	600	210	10	64.3	107.1	136.5	1400	29410
GU 15N	600	211	11	68.7	114.5	145.9	1530	32260
GU 16N	600	215	10.2	72.6	121.0	154.2	1670	35950
GU 18N	600	215	11.2	76.9	128.2	163.3	1800	38650

U-Type Hot-Rolled Piles	W mm	H mm	T mm	Unit Mass kg/Lin m	Unit Mass kg/m ² *	Sectional Area cm ² /m*	Section Modulus cm ³ /m*	Moment of Inertia cm ⁴ /m*
GU 20N	600	215	12.2	81.1	135.2	172.3	1920	41320
GU 21N	600	225	11.1	81.9	136.5	173.9	2060	46380
GU 22N	600	225	12.1	86.1	143.6	182.9	2200	49460
GU 23N	600	225	13.1	90.4	150.7	192	2335	52510
GU 27N	600	226	14.2	97.4	162.3	206.8	2680	60580
GU 28N	600	227	15.2	101.8	169.6	216.1	2840	64460
GU 30N	600	228	16.2	106.2	177.1	225.6	3000	68380
GU 31N	600	226	18.5	109.9	183.2	233.3	3065	69210
GU 32N	600	226	19.5	114.1	190.2	242	3200	72320
GU 33N	600	226	20.5	118.4	197.3	251.3	3340	75410
GU 16-400	400	145	12.7	62.0	154.9	197.3	1560	22580
GU 18-400	400	146	15	69.3	173.3	220.8	1785	26090

*Per 1m of pile wall width